



Egret Double Sided Scrim Tape

EGDSS-200

SECTION 1: DESCRIPTION & BENEFITS

- Use high duty fiber glass(PES/PVS) mesh cloth as backing
- Both sides coated with aggressive pressure sensitive adhesive
- Protected by gold glassine paper release liner
- Backing material has very good tensile strength
- Extremely high adhesion strength
- Can be removed with no glue residue & no de-lamination
- Excellent resistance to abrasion, moisture, high temperature
- Can easily conform to many irregular surfaces



SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Backing color	Transparent	Visual
Total Thickness	200 microns (8.0 mil)	PSTC-133/ASTM D3652
180° Peel Adhesion	≥ 25 N/25mm (90.0 Oz/In)	PSTC-101/ASTM D3330
Glue Type	Water based acrylic	
Static Shear	≥ 48 hrs	GB/T4851-2014
Tensile Strength	≥ 50 N/25mm (13.6 Lb/In)	PSTC-131/ASTM D3759
Elongation at Break	9.0%	PSTC-6/ASTM D3121
Material	PES/PVS diagonal scrim	
Service Temp.	-10 ~ 120°C (14 ~ 248 ° F)	
Operating Temp.	0 ~ +40°C (+32 ~ +105 ° F)	

SECTION 3: APPLICATIONS & OTHER DETAILS

- Laminating foams, plastic films
- Bonding materials such as fabrics, plastic, metal, wood, etc.
- Fixing furniture and curtains



Standard width: 8,10,15,20,30,50 mm; **Standard length:** 20m, 50m

Jumbo roll: 1000(usable) mm x 50m, etc

Tolerance: Thickness: +/- 10% Width: +/-1.0mm Length: +/- 0.4m

Storage: Indoor storage: 10°C-28°C, humidity:<80%, cool & dry, free of direct sunlight

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com



Egret Double Sided Scrim Tape

EGDSS-200

Shelf Life: 6 months in room temp. We recommend you use out in 3 months, to reach best condition of tape.

***N.B.** Performance data above are conducted in Egret lab, based on PSTC/ASTM/GB methods. It can only be treated as a reference, we don't guarantee the accuracy. Individual rolls might vary from these data, due to different environment, test methods, equipment. Pls advise our sales regarding your application, so that we can give you best recommendation.

Please keep the operating surface clean, dry, and free of grease or other dirt/dust. So that **Egret Tape** can reach a best result.

www.egretmfg.com

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com