



# Egret ® NBR foam Tape

# EGNBR-2

## SECTION 1: DESCRIPTION & BENEFITS

- 2mm high-density closed-cell NBR foam as carrier
- Coated with special formula of very high tack adhesive
- Laminated with yellow paper easy release liner
- Excellent properties of high elasticity
- Outstanding aging resistance, oil resistance
- Good high temperature resistance
- Great air sealing, moisture sealing
- Outstanding conformity to uneven surfaces



## SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Carrier Color	Black	Visual
Liner Color	Yellow	Visual
Density	≥ 200 KG/m <sup>3</sup>	ASTM D-3575
Peel Adhesion	≥ 6 N/CM	ASTM D-3330
Loop Tack	16 # steel ball	GB/T 4852-84
Tensile strength	20 N/CM	ASTM D3759
Elongation	≥ 180%	ASTM D-3330
Temp Resistance	-30°C~80°C	

## SECTION 3: APPLICATIONS & OTHER DETAILS

- Packaging cushion material
- Civil building thermal insulation
- HVAC thermal insulation
- Home appliance acoustic dampening

Sliced roll width available (or customized): 10-1600mm

Standard Length: 100-2000mm

Tolerance: Thickness: +/- 10%    Width: +/-1.0mm    Length: +/- 0.4m

Storage: Indoor storage: -5°C-40°C (humidity: < 80%), cool & dry, free of direct sunlight

Shelf Life: 12 months in room temp.



**N.B.** Please keep the operating surface clean, dry, and free of grease or other dirt & dust. So that **Egret Tape** can have a best performance.

**Changzhou Egret Manufacturing Co., Ltd**

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807    Email: info@egretmfg.com    Website: www.egretmfg.com